

EVO[®] 5 DUALSWITCH™

PRODUCT CODE: AKS270-000-100

EVO[®]5 DUALSWITCH™ HAS THE ABILITY TO SWITCH BETWEEN EN397 & EN12492 USING THE SWITCHABLE ANCHORAGE CHINSTRAP

TECHNICAL
SPECIFICATION

HEAD PROTECTION



MATERIALS

Shell: ABS (Acrylonitrile Butadiene Styrene)

Harness: LDPE (Low Density Polyethylene) Strap & Webbing Clips with Polyester Webbing Straps

Liner: EPP (Expanded Polypropylene)

GENERAL INSTRUCTIONS FOR USE

Ensure switchable anchorage is set to required standard (EN397/EN12492). Switch up for EN397, switch down for EN12492.

Fit the helmet on the head, adjust wheel ratchet and chinstrap, and tuck free end of chinstrap under rubber O-ring

For adequate protection the helmet must be worn with peak facing forward



GENERAL CLEANING & MAINTENANCE

The helmet may be cleaned with soap and warm water and dried with a soft cloth

The helmet should not be cleaned with chemical or abrasive cleaners

The helmet should be stored out of direct sunlight

The helmet should be stored away from chemicals and extremes of temperature

CONFORMITY & PERFORMANCE

Conforms to EN397 for Industrial Safety Helmets and EN12492 for Mountaineering Helmets

Conforms to EN50365 for Helmets for use in low voltage installations when in EN397 configuration

EC Certificate Number 601644, issued by BSi Product Certification

Meets optional Lateral Deformation performance

Wide size range suitable for all head shapes

